

Sling

Leather Pull



spinneybeck



Leather Pulls are all about the details.

Leather Pulls are die cut from 100 percent vegetable tanned, full grain Belting Leather in oodles of colorways ranging from natural to vibrant hues. The sculptural shapes are enhanced by the inherent qualities of Belting Leather—its thick, firm feel and smooth finish are tactile yet substantive. Pulls feature a protective water resistant finish making them suitable for home, corporate, retail, hospitality, or educational environments. And installation is a snap with stainless steel mounting hardware provided.

Sling Pull was designed by Emanuela Frattini Magnusson, founder and principal of EFM Design, an international, award-winning, multi-disciplinary practice that spans architecture, interiors, product design, brand development, and graphics.



"I love leather because of its tactile and olfactory qualities. Contrary to its perception of exclusivity and preciousness, leather is often the practical choice for its durability and resistance. Leather combines the highest aesthetic results with built-in durability that is often the most effective solution when considering the long-term view."

– Emanuela Frattini Magnusson, designer of Sling Pull

Product	Sling Pull
Designer	Emanuela Frattini Magnusson
Content	European cowhide
Sizes	Small: 7/8 x 5 1/2 in (2.2 x 14 cm) Large: 1 1/4 x 13 1/2 in (3.2 x 34.3 cm) X-Large: 1 1/4 x 18 in (3.2 x 45.7 cm)
Leather Type	Belting Leather (BL)
Leather Thickness	0.11–0.12 in (2.8–3.2 mm)
Finish	Light, protective water resistant
Custom	Custom shapes are available and cost of custom die must be quoted
Durability	Contract or residential
Lead Time	Made to order and certain lead times will apply
Standard Hardware	Four socket head cap screws + acorn nuts per small or large pull or two 1 1/4 in (3.2 cm) stainless steel light duty binding posts per x-large pull
Custom Hardware	Standard hardware length for binding posts and screws is 1 1/4 inch (3.2 cm). Additional sizes are available. An upcharge per pull applies to orders requiring binding posts or cap screws longer than 2 in (5 cm).
Installation	Install with hardware provided and mount to a clean and dry surface. Large and Extra-Large may be mounted flush or looped.
Maintenance	Wipe entire surface with a soft cloth and cool water to even out any abrasions or stains. Do not spot rub, for it will darken only that area. Occasional use of Spinneybeck Aniline Leather Cleaner, Conditioner & Protector is recommended. Other leather cleaners such as saddle soap or household cleaners that may contain harsh chemicals, alcohol or ink removers should never be used.

Standard Colors

